


# TL4

## series



### Product Segments

#### • Ergo Motion


TiMOTION's TL4 series lifting columns are specifically designed for use in ergonomic desks and work tables. Using multiple TL series lifting columns with compatible TC series Control Boxes and TH / TDH series controls, work surfaces can be controlled quietly and smoothly with synchronous movement. All Ergo Motion TC series control boxes have a less than 0.1W standby power option that reduces power consumption. Our wide range of columns offer customers the solutions they require to satisfy their working environment project requirements. The TL4 has a three stage telescopic outer tube that is designed for a narrow-top, wide-bottom square appearance.

#### General Features

Max. load	800N (push)
Max. speed at max. load	33mm/s
Max. speed at no load	58mm/s
Retracted length	With foot: 590 / 560 (M) / 520 (S) mm Excluding shoes: 610 / 580 (M) / 540 (S) mm
Dimension of outer tube	3-stage, 70*70mm square
Stroke	650 / 660 (M, S) mm
Color	Black, white, grey, or special grey

## Drawing

Standard Dimensions  
(mm)



## Load and Speed

CODE	Load (N)	Self Locking Force (N)	Typical Current (A)		Typical Speed (mm/s)	
	Push		No Load 32V DC	With Load 24V DC	No Load 32V DC	With Load 24V DC
Motor Speed (5200RPM)						
C	800	800	2.8	6.0	58.0	33.0


## Note

- 1 This self-locking force level is reached only when a short circuit is applied on the terminals of the motor. All the TiMOTION control boxes have this feature built-in.
- 2 Parameters above are from tested average, please refer to approval drawing for final value.


## Performance Data (24V DC Motor)

Motor Speed (5200RPM)

Speed vs. Load



Current vs. Load



### Note

<sup>1</sup> The performance data in the curve charts shows theoretical value.

<b>Appearance of Tubes</b>	C = Without wiper fixing holes at sides		
<b>Voltage</b>	2 = 24V DC		
<b>Load and Speed</b>	<a href="#">See page 2</a>		
<b>Stroke &amp; Retracted Length (mm)</b>	<a href="#">See page 5</a>		
<b>Color</b>	1 = Black, RAL 9005, Black wiper 2 = Grey, RAL 9006, Black wiper 3 = White, RAL 9016, Black wiper 4 = Special grey, RAL 9022, Black wiper 6 = Grey, RAL 9006, Grey wiper	7 = White, RAL 9016, White wiper 8 = Special grey, RAL 9022, Grey wiper B = Matte black, RAL 7021, Black wiper C = Graphite grey, RAL7024, Black wiper D = Matte black, RAL 7021, Matte Black wiper	
<b>Motor Housing Step</b>	0 = With	1 = Without	
<b>Output Signals</b>	2 = Hall sensor*2		
<b>Connector</b>	1 = DIN 6P, 90° plug E = Molex 8P, 180° plug, standard	F = Molex 8P, 90° plug, without anti-clip, for TC22 / TC23	
<b>Cable Length (mm)</b>	1 = Straight, 500	3 = Straight, 1000	4 = Straight, 1500
<b>Bracket</b> <a href="#">See page 5</a>	0 = Without L = Left, Standard bracket R = Right, Standard bracket	B = Back, Standard bracket (For wall mounting application)	

### Note

<sup>1</sup> The TL is designed especially for push applications, not suitable for pull applications.


Stroke & Retracted Length (mm)

Foot Assembly	Stroke & Retracted Length		
	Standard	M	S
Standard, with Foot	650 / 590	660 / 560	660 / 520
Extended Outer Tube for Shoe (Excluding Shoe)	650 / 610	660 / 580	660 / 540

Note


1 Only specific TEK could be with the shoes, please refer to TEK speccode

Foot Assembly




Bracket

Standard direction




Connector


1 = DIN 6P, 90° plug



E = Molex 8P, 180° plug, standard



F = Molex 8P, 90° plug, without anti-clip, for TC22 / TC23



Terms of Use

The user is responsible for determining the suitability of TiMOTION products for a specific application. TiMOTION products are subject to change without prior notice.