SMART3 • QUICK START GUIDE

LAN	OTTE PRE-PROGRAMMED TESTS
1.	Press and briefly hold 🖒 to turn meter on. Main Menu will appear.
2.	Press enter to select Testing Menu.
3.	Press enter to select All Tests menu.
4.	Press or to scroll to the desired test.
5.	Press enter to select the test.
6.	Insert the blank. Close the lid. Press enter to scan the blank.
7.	Insert the reacted sample. Close the lid. Press to scan the sample. The result will appear on the screen.

ADD	OR DELETE A TEST IN A SEQUENCE
1.	Press and briefly hold 🖒 to turn meter on. Main Menu will appear.
2.	Press or to the Editing Menu. Press (ENTER).
3.	Press to select Edit Sequences.
4.	Press or to scroll to the desired sequence and press enter.

Add A	Add A Test	
5.	To add a test before or after an existing test, press or to scroll to the existing test.	
6.	Press to select the existing test. Press or to scroll to Insert Before or Insert After.	
7.	Press to select the option. The All Tests menu will appear.	
8.	Press or to scroll to the test that will be added to the sequence.	
9.	Press to select the test. The test will be added to the sequence.	

Delet	e A Test
5.	To delete a test, press or to scroll to the test in the sequence.
6.	Press to select the test. Press or to scroll to Delete .
7.	Press to select Delete . The test will be deleted from the sequence.

٠.	Press or to scroll to the desired test. Press (NIE).
Nam	e The Test
5.	Press to select Name The Test.
6.	Press , wand extent to select the characters in the test name.
7.	Press after the last character has been selected.

Selec	ct Vial/WL
8.	Press or to select Vial/WL. Press enter.
9.	Press or to scroll to the channel with the desired wavelength and vial size combination. Press (NTER).
Enter	² Point Calibration

Enter	r 2 Point Calibration
10.	Press or to scroll to STD Calibration. Press (NTER).
11.	Press , and enter to select the characters in the low concentration followed by the high concentration. Press enter.
12.	Insert the blank. Press (NTE). Repeat with reacted low and high concentration standards. Press (NTE).

Selec	ct Decimal Places
13.	Press or to scroll to Decimal Places . Press
14.	Press , and to select the desired number of decimal places.

Sele	ct Units
15.	Press or to scroll to Select Units. Press enter.
16.	Press or to select the desired units. Press The meter will return to the Edit Test menu. Press Three times to return to the Main Menu to begin testing.

NOTE: Use the AC wall adapter to rapidly charge the meter.

