



415 S Airpark Road  
Cottonwood, AZ 86326, USA  
Phone: (800) 733-0266  
Fax: (928) 649-2306  
Email: info@prelaboratories.com

## Product Technical Fact Sheet

Product Code: CHL-2000

Product Description: Active Chlorine Test Strips 0-2000 ppm

### Application:

The 0-2000 ppm Active Chlorine test strip is used for testing sanitization and disinfecting levels of free chlorine in water. The Active Chlorine test strips can be used in facilities where food preparation areas, equipment, and general disinfection are strictly controlled.

Test Range: 0-2000 ppm

Test Increments: Color chart calibrated at 0, 25, 50, 200, 500, 800, 1500, and 2000 ppm

Accuracy: +/- ½ color chart unit

Detection Limit: 12.5 ppm

### Storage Recommendations:

Store in original packaging in a cool (20-30C), dry, place out of direct sunlight.

Shelf-Life: Two years from date of manufacture when stored properly in original packaging.

Interferences: Test strip may react to other oxidizing materials, peracetic acid, peroxide, etc.

### Instructions for Use:

1. Dip the Active Chlorine test strip into solution for 1 second.
2. Remove strip and shake off excess water.
3. After 1 minute, compare pad against color chart. (Note: color on the pad may not be uniform; this is normal.)

### Chemistry Behind the Test:

The test pad is treated with a formula consisting of buffers, surfactants, and red-ox indicators. The presence of free chlorine in a sample causes the red-ox indicator in the test pad to develop color. The intensity of the color developed is proportional to the amount of free chlorine present.

### Other Information:

The Active Chlorine test strips were developed to work with solutions prepared from concentrated solutions of sodium hypochlorite.

### Disclaimer:

The Active Chlorine test strips are not intended for use to diagnose, treat, or monitor any medical condition.