

MX-S

Variable speed Vortex Mixer

Features

- Variable speed of 0 to 3,000rpm for gentle shaking to rapid mixing of samples
- Touch or continuous operation mode
- Includes a standard top head for mixing a single test tube or other small vessel up to 30mm in diameter
- Electronic speed control maintains constant speed even during changes in load
- Steel base with specially designed vacuum suction feet provides stability and dampens vibration
- · Robust aluminum-cast construction



VT1.1 Standard top(Default) Cat. No.18900034

for <Ø30mm tubes and small vessels



Specifications	MX-S (Adjustable speed)
Voltage,Frequency	100-120V/200-240V,50/60Hz
Power	60W
Mixing motion	Orbital
Orbital diameter	4mm
Motor type	Shaded pole motor
Motor rating input	58W
Motor rating output	10W
Speed range	0-3000rpm
Speed display	Scale
Run type	Touch operation/Continuous
$Dimension[W \times H \times D]$	127×130×160mm
Weight	2.0kg
Permissible ambient temperature	5-40°C
Permissible relative humidity	80%RH
Protection class	IP20



VT1.3.1 tube adapter

Cat. No.18900020

for 48 test tubes, Ø6mm (1mL)



VT1.3.10 tube adapter

for 4 holes test tubes, Ø28mm (50mL)



VT1.3.2 tube adapter

Cat. No.18900021

for 15 test tubes, Ø10mm (1.5-2mL)



VT1.3.11 Tube adapter

12XØ9.8mm+12XØ6.6mm+12XØ5mm (1.5/2.0/0.5/0.2mL)



VT1.3.3 tube adapter

Cat. No.18900022

for 16 test tubes, Ø12mm (5mL)



VT1.2 Tube holding rod

used with tube adapters



VT1.3.4 tube adapter

Cat. No.18900023

for 8 test tubes, Ø16mm (10mL)

VT1.3 Universal top plate

Ø 100mm Includes 4 vacuum chuck



VT1.3.5 tube adapter

Cat. No.18900024



PS1.0 Microplate clamp

Includes rectangle PCR tube adapter



for 8 test tubes, Ø20mm (10-15mL)



Cat. No.18900875

VT1.3.6 Platform pad

Cat. No.18900043

Ø99mm, multiple small tubes and vessels



Cat. No.18900158

VT1.3.12 Large Platform

Multi-Specimen Test Tube Adapter

44 holesXØ5mm+55 holesXØ6.6mm+30 holesXØ9.8mm (1.5/2.0/0.5/0.2mL)



VT1.3.7 vacuum chuck

made of rubber



VT1.4 Ampule/Tube Attachment

4pc ampule/tube (0.2mL-15mL)



VT1.3.8 tube adapter

for 24 holes test tubes, Ø 10mm (1.5-2mL)



VT1.5 Erlenmeyer flask attachment

100mL-250mL, Operating speed: 0~1500rpm





VT1.3.9 PCR tube adapter

for 56 test PCR tubes, strips of 8, Ø5mm (0.1mL-0.5mL)



Cat. No.18204185

















Application of accessories

Accessories	Adjustable speed model (0-2500rpm)	
	Touch mode (High speed area)	Continuous mode (Low speed area)
VTI.1	Υ	Υ
VTI.2 + VT1.3.1	Υ	
VTI.2 + VT1.3.2	Υ	
VTI.2 + VT1.3.3	Υ	
VTI.2 + VT1.3.4	Υ	
VTI.2 + VT1.3.5	Υ	
VTI.3 + VT1.3.6	Υ	
VTI.3 + VT1.3.1		Υ
VTI.3 + VT1.3.2		Υ
VTI.3 + VT1.3.3		Υ
VTI.3 + VT1.3.4		Y
VTI.3 + VT1.3.5		Υ